

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application

Listing of Claims:

1. (Currently Amended) A display device comprising:

a display part made of a roll-up~~7~~-sheet-like direct-view display element;

a take-up part attached on one end of the display part, the take-up part allowing the display part to be ~~rolled~~rolled up;

a pulling part attached on an other end of the display part, the pulling part allowing the display part to be ~~roll~~rolled out; and

a holding part for holding the display part from behind, wherein

the holding part is formed of linkage, which are stored on a rear surface of the display part when the display part is rolled up, and are stretched across the rear surface of the display part when the display part is rolled out; and

the linkage includes:

~~at least two rails; and~~

a first rail having a first end and a second rail having a second end, the first rail and the second rail crossing each other

a rail intersection for rotatably supporting the two first rail and the second rail rails at a center of the two rails point where the first rail and the second rail cross each other,

the first end being slidable within the pulling part and the second end being slidable within the take-up part.

2. (Currently Amended) The display device of claim 1, wherein:

~~the linkage includes two rails crossing in a shape of an X; and~~

the first rail further includes a third end and the second rail further includes a fourth end, and

the take-up part and the pulling part each comprise:

a first rail support for rotatably supporting the fourth end and the third end,
~~respectively one end of one of the rails rotatably;~~ and

a second rail support for rotatably and slidably supporting the other first end and the second end, respectively of the rail rotatably and slidably.

3. (Currently Amended) The display device of claim 1, wherein:

the first rail further includes a third end and the second rail further includes a fourth end, and

~~the linkage includes a first rail and a second rail crossing in a shape of an X;~~

the ~~take-up~~pulling part includes:

a first rail support for supporting ~~one the fourth end of the first rail~~ rotatably; and

a second rail support for supporting ~~one end of the second rail~~the first end
rotatably and slidably;

the pulling~~take-up~~ part includes:

~~the first a third~~ rail support for supporting the ~~other end of the second rail~~third
end rotatably, and

~~the second a fourth~~ rail support for supporting the other end of the first rail~~second~~
end rotatably and slidably.

4. (Cancelled)

5. (Previously Presented) The display device of claim 2, wherein

the take-up part and the pulling part further each include an elastic member, the elastic member biasing the slidable second rail support in a direction away from the first rail support.

6. (Original) The display device of claim 1, wherein

the display part includes a first joint part on the rear surface thereof;

the holding part includes a second joint part; and

the first joint part and the second joint part face each other when the display part is spread out.

7. (Original) The display device of claim 6, wherein

at least one of the first joint part and the second joint part is one of a magnet and an electromagnet, and

the first joint part and the second joint part attract magnetically.

8. (Original) The display device of claim 1, wherein

at least one of the take-up part and the pulling part is provided at a side end thereof with a bending part which is bent backward; and

the display part can be bent by bending the bending part.

9. (Previously Presented) The display device of claim 1, wherein

the take-up part includes a power circuit for supplying power to the display part and an audiovisual circuit for supplying an audiovisual signal to the display part;

the holding part includes a power wiring for supplying the power to the power circuit and an audiovisual wiring for supplying the audiovisual signal to the audiovisual circuit; and

the power supply wiring and the audiovisual wiring are connected to an external power supply and an audiovisual device via a connecting part provided in the pulling part.

10. (Cancelled)

11. (Previously Presented) The display device of claim 3, wherein

the take-up part and the pulling part further each include an elastic member, the elastic member biasing the slidable second rail support in a direction away from the first rail support.

12.-14. Cancelled